



ENLARGED VIEW OF  
SHAFT EXTENSION  
(SCALE 1:2)

4 HOLES FOR .750 BOLTS

2 LIFTING LUGS  
DIAGONALLY OPPOSITE

NOTE: -  
TERMINAL BOX CAN BE TOP OR RIGHT  
HAND SIDE MOUNTED BY REFITTING FEET  
90° IN APPROPRIATE DIRECTION.  
CABLE ENTRY CAN BE SUPPLIED IN  
ANY ONE OF FOUR POSITIONS AT  
90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BGRS.	DE.	NDE.
MOTOR NETT. WT. Kg.		
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS,	VOLTS	

REMARKS

CSA APPROVED

NOTE!  
FITTED WITH SPECIAL  
FEET W-DF447T

ALL DIMENSIONS IN INCHES

THIRD ANGLE  
PROJECTION

**BROOK  
CROMPTON**

NOTE 1  
\* ENDPLAY WILL BE PROVIDED FOR ENDTHRUST  
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR  
INTENTION TO USE RIGID COUPLINGS AND DRIVEN  
MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A. C. MOTOR  
TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.  
FITTED WITH SIDE MOUNTED TERMINAL BOX  
FRAME SIZE :- W-DF447T-N

SCALE	18	DATE
DRAWN	SW	6.9.99
CHECKED	JML	6.9.99
APPROVED	JML	6.9.99

DRG. No.	M21696	
REVISION:		DATE