



NOTE!
 TERMINAL BOX CAN BE SIDE MOUNTED (LEFT OR RIGHT) BY REFITTING FEET 90° IN APPROPRIATE DIRECTION. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90° INTERVALS.

| | | |
|----------------------------------|---------|---------|
| CUSTOMER | | |
| ORDER No. | | |
| SERIAL No. | | |
| FRAME SIZE | | |
| Kw | R.P.M. | |
| Hz | PHASE 3 | |
| VOLTS | POLES | |
| BRGS. | D.E | N.D.E |
| MOTOR NETT. WT. | | Kg. |
| INSULATION CLASS | | |
| TEMPERATURE RISE | | ° C |
| DESIGN AMBIENT TEMPERATURE | | ° C |
| HEATER WATTS & VOLTS (IF FITTED) | | |
| - WATTS, | | - VOLTS |

REMARKS

ALL DIMENSIONS IN MILLIMETRES

FIRST ANGLE PROJECTION

BROOK CROMPTON

NOTE!
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A.C. MOTOR
 TOTALLY ENCLOSED FAN VENTILATED.
 FRAME SIZE:- W-DF355L 4-POLE UP.

| | | |
|----------|------|------|
| SCALE | 1:10 | DATE |
| DRAWN | | |
| CHECKED | | |
| APPROVED | | |

| | | |
|-----------|--|------|
| DRG. No. | | |
| REVISION: | | DATE |