



NOTE: -
 TERMINAL BOX CAN BE SIDE MOUNTED
 (LEFT OR RIGHT) BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
kW	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.		Kg.
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		WATTS, VOLTS

REMARKS	
 Large Industrial Motors Guiseley, LEEDS LS20 9NZ	

ALL DIMENSIONS IN MILLIMETRES

FIRST ANGLE PROJECTION

Large Industrial Motors
 GUISELEY, LEEDS, LS20 9NZ.

NOTE 1
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A. C. MOTOR
 TOTALLY ENCLOSED FAN VENTILATED.
 FRAME SIZE : - W-DF200L (ALL POLES)

SCALE	1:6	DATE	DRG. No.
DRAWN	JML	31/03/93	M9105
CHECKED	B. J. T.	31/03/93	
APPROVED	I. J. W.	31/03/93	REVISION: A M E DATE 18. 9. 97