



NOTE: -
 TERMINAL BOX CAN BE SIDE MOUNTED
 (LEFT OR RIGHT) BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

| | | |
|----------------------------|---------|-------|
| CUSTOMER | | |
| ORDER No. | | |
| SERIAL No. | | |
| FRAME SIZE | | |
| kW | RPM. | |
| Hz | PHASE 3 | |
| VOLTS | POLES | |
| BRGS. | DE. | NDE. |
| MOTOR NETT. WT. | Kg. | |
| INSULATION CLASS | | |
| TEMPERATURE RISE | ° C | |
| DESIGN AMBIENT TEMPERATURE | ° C | |
| HEATER WATTS & VOLTS | | |
| | WATTS, | VOLTS |

REMARKS

ALL DIMENSIONS IN MILLIMETRES



BROOK CROMPTON

NOTE 1
 2.5 ENDFLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDFLAY.

OUTLINE DIMENSIONS OF STD. FOOT/FLANGE MOUNTED METRIC A. C. MOTOR
 TOTALLY ENCLOSED FAN VENTILATED.
 FITTED WITH TOP MOUNTED TERMINAL BOX
 FRAME SIZE : - W-DF315S-H (4 POLE UP)

| | | |
|----------|-----|------|
| SCALE | 1:8 | DATE |
| DRAWN | | |
| CHECKED | | |
| APPROVED | | |

| | | |
|-----------|--|------|
| DRG. No. | | |
| REVISION: | | DATE |