



CUSTOMER	
ORDER No.	
SERIAL No.	
FRAME SIZE	
KW	R.P.M.
Hz	PHASE 3
VOLTS	POLES
BRGS.	D.F. N.D.F.
MOTOR NETT. WT.	Kg.
INSULATION CLASS	
TEMPERATURE RISE °C	
DESIGN AMBIENT TEMPERATURE °C	
HEATER WATTS & VOLTS (IF FITTED)	
- WATTS, - VOLTS	

REMARKS

ALL DIMENSIONS IN MILLIMETRES

FIRST ANGLE PROJECTION

**BROOK CROMPTON**

NOTE:-  
 TERMINAL BOX CAN BE MOUNTED TOP OR LEFT HAND SIDE BY REFITTING FEET AND LIFTING LUGS 90 ° IN APPROPRIATE DIRECTIONS. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90 ° INTERVALS

NOTE!  
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A.C. MOTOR  
 TOTALLY ENCLOSED FAN VENTILATED.  
 TERMINAL BOX MOUNTED ON RIGHT HAND SIDE VIEWED ON DRIVE END.  
 FRAME SIZE: W-DF355L (4 POLE UP).

SCALE	1:1	DATE
DRAWN		
CHECKED		
APPROVED		

DRG. No.	
REVISION:	DATE