



CUSTOMER	
ORDER No.	
SERIAL No.	
FRAME SIZE	
KW	R.P.M.
Hz	PHASE 3
VOLTS	POLES
BRGS.	D.F. N.D.F.
MOTOR NETT. WT.	Kg.
INSULATION CLASS	
TEMPERATURE RISE °C	
DESIGN AMBIENT TEMPERATURE °C	
HEATER WATTS & VOLTS (IF FITTED)	
- WATTS, - VOLTS	

REMARKS

ALL DIMENSIONS IN MILLIMETRES

FIRST ANGLE PROJECTION

**BROOK CROMPTON**

NOTE:-  
 TERMINAL BOX CAN BE MOUNTED TOP OR LEFT HAND SIDE BY REFITTING FEET AND LIFTING LUGS 90 ° IN APPROPRIATE DIRECTIONS. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90 ° INTERVALS

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A.C. MOTOR  
 TOTALLY ENCLOSED FAN VENTILATED.  
 TERMINAL BOX MOUNTED ON RIGHT HAND SIDE VIEWED ON DRIVE END.  
 FRAME SIZE: W-DF355L (2 POLE ONLY).

SCALE	1:1	DATE
DRAWN		
CHECKED		
APPROVED		

DRG. No.	
REVISION:	DATE

NOTE:  
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.