



SECTION THROUGH
SHAFT EXTENSION.
(SCALE 1:2).

NOTE:-
CABLE ENTRY CAN BE
SUPPLIED IN ANY ONE OF FOUR
POSITIONS AT 90° INTERVALS.

NOTE:-
TERMINAL BOX CAN BE MOUNTED
(TOP OR RIGHT) BY REFITTING FEET
AND LIFTING LUGS 90° IN APPROPRIATE
DIRECTIONS. CABLE ENTRY CAN BE
SUPPLIED IN ANY ONE OF FOUR
POSITIONS AT 90° INTERVALS.

NOTE1
ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
INTENTION TO USE RIGID COUPLINGS AND DRIVEN
MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A.C
MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN VENTILATED.
TERMINAL BOX MOUNTED ON LEFT HAND SIDE VIEWED ON DRIVE END.
FRAME SIZE. W-DF324T-X (4 POLE UP).

SCALE	1:6	DATE	
DRAWN	M.E	0.11.99	
CHECKED	J.M.L	0.11.99	
APPROVED	J.M.L	0.11.99	

CUSTOMER	
ORDER No.	
SERIAL No.	
FRAME SIZE	
KW	R.P.M.
Hz	PHASE 3
VOLTS	POLES
BRGS. DE	N.D.E
MOTOR NETT. WT.	Kg.
INSULATION CLASS	
TEMPERATURE RISE °C	
DESIGN AMBIENT TEMPERATURE °C	
HEATER WATTS & VOLTS (IF FITTED)	
- WATTS, - VOLTS	
REMARKS	



ALL DIMENSIONS IN INCHES



THIRD ANGLE
PROJECTION

**BROOK
CROMPTON**

Large Industrial Motors
GUISELEY, LEEDS, LS20 9NZ.

DRG. No.	M21640
REVISION:	DATE