



4 HOLES FOR .750 BOLTS

NOTE: -
 TERMINAL BOX CAN BE TOP OR RIGHT
 HAND SIDE MOUNTED BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.	Kg.	
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS,		VOLTS

REMARKS

BROOK CROMPTON
 PRELIMINARY

Large Industrial Motors
 Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES



BROOK CROMPTON

Large Industrial Motors
 GUISELEY, LEEDS, LS20 9NZ.

NOTE !
 * ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A. C. MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED. FITTED WITH SIDE MOUNTED TERMINAL BOX FRAME SIZE :- W-DF445T-N (4 POLE UP)

SCALE	1:8	DATE
DRAWN	B. J. T.	8.2.94
CHECKED	B. J. T.	8.2.94
APPROVED	I. J. W.	8.2.94

DRG. No.	M9516
REVISION:	DATE