



NOTE: -
 TERMINAL BOX CAN BE TOP OR RIGHT
 HAND SIDE MOUNTED BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A. C. MOTOR
 TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.
 FITTED WITH SIDE MOUNTED TERMINAL BOX
 FRAME SIZE: W-DF445T-E (4 POLE UP.)

| | | | |
|----------|-------|--------|--|
| SCALE | 1:8 | DATE | |
| DRAWN | M.E | 5.7.00 | |
| CHECKED | J.M.L | 5.7.00 | |
| APPROVED | J.M.L | 5.7.00 | |

| | | |
|-------------------------------|---------|-------|
| CUSTOMER | | |
| ORDER No. | | |
| SERIAL No. | | |
| FRAME SIZE | | |
| kW | RPM. | |
| Hz | PHASE 3 | |
| VOLTS | POLES | |
| BRGS. | DE. | NDE. |
| MOTOR NETT. WT. | | Kg. |
| INSULATION CLASS | | |
| TEMPERATURE RISE °C | | |
| DESIGN AMBIENT TEMPERATURE °C | | |
| HEATER WATTS & VOLTS | | |
| | WATTS, | VOLTS |

REMARKS

BROOK CROMPTON
 PRELIMINARY

Large Industrial Motors
 Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES

THIRD ANGLE PROJECTION

BROOK CROMPTON

Large Industrial Motors
 GUISELEY, LEEDS, LS20 9NZ.

NOTE 1
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

| | |
|-----------|--------|
| DRG. No. | M22082 |
| REVISION: | DATE |