



SECTION THROUGH
SHAFT EXTENSION.
(SCALE 1:2).

NOTE:-
CABLE ENTRY CAN BE
SUPPLIED IN ANY ONE OF FOUR
POSITIONS AT 90 ° INTERVALS.

NOTE:-
TERMINAL BOX CAN BE MOUNTED
(TOP OR RIGHT) BY REFITTING FEET
AND LIFTING LUGS 90 ° IN APPROPRIATE
DIRECTIONS. CABLE ENTRY CAN BE
SUPPLIED IN ANY ONE OF FOUR
POSITIONS AT 90 ° INTERVALS.

CUSTOMER	
ORDER No.	
SERIAL No.	
FRAME SIZE	
KW	R.P.M.
Hz	PHASE 3
VOLTS	POLES
BRGS. D.E	N.D.E
MOTOR NETT. WT.	Kg.
INSULATION CLASS	
TEMPERATURE RISE °C	
DESIGN AMBIENT TEMPERATURE °C	
HEATER WATTS & VOLTS (IF FITTED)	
- WATTS,	- VOLTS

REMARKS

Large Industrial Motors
Guisley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES

THIRD ANGLE
PROJECTION

Large Industrial Motors
GUISLEY, LEEDS, LS20 9NZ.

NOTE!
ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
INTENTION TO USE RIGID COUPLINGS AND DRIVEN
MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED INCH A.C
MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN VENTILATED.
TERMINAL BOX MOUNTED ON LEFT HAND SIDE VIEWED ON DRIVE END.
FRAME SIZE. W-DF324TS-X (2 POLE ONLY).

SCALE	1:6	DATE	DRG. No.
DRAWN	M.E	1.9.99	M21646
CHECKED	J.M.L	1.9.99	-
APPROVED	J.M.L	1.9.99	REVISION: DATE