



ENLARGED VIEW OF SHAFT EXTENSION.

4 HOLES FOR .625 BOLTS

NOTE: -
 TERMINAL BOX CAN BE TOP OR RIGHT
 HAND SIDE MOUNTED BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.	Kg.	
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS,		VOLTS

REMARKS

BROOK CROMPTON
 PRELIMINARY

Large Industrial Motors
 Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES



BROOK CROMPTON

Large Industrial Motors
 GUISELEY, LEEDS, LS20 9NZ.

NOTE !
 * ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/C FACE MOUNTED INCH A. C. MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED. FITTED WITH SIDE MOUNTED TERMINAL BOX
 FRAME SIZE: - WNDF364T.

SCALE	1:6	DATE
DRAWN	B.Thomas	17.6.94
CHECKED	B.J.T.	17.6.94
APPROVED	I.J.W.	17.6.94

DRG. No.	M9707	
REVISION:		DATE