



MAINS CABLE ENTRY
SCREWED 3" N. P. T.

NOTE 1
2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

NOTE! TERMINAL BOX CAN BE TOP MOUNTED BY REFITTING FEET 90° IN APPROPRIATE DIRECTION. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90° INTERVALS.

OUTLINE DIMENSIONS OF STANDARD FOOT/C FACE MOUNTED INCH A. C. MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED. FITTED WITH SIDE MOUNTED TERMINAL BOX. FRAME SIZE: W-DF445TC-E (4 POLE UP.)

SCALE	1:8	DATE	
DRAWN	M.E	6.7.00	
CHECKED	J.M.L	6.7.00	
APPROVED	J.M.L	6.7.00	

CUSTOMER			
ORDER No.			
SERIAL No.			
FRAME SIZE			
kW		RPM.	
Hz		PHASE	3
VOLTS		POLES	
BRGS.	DE.	NDE.	
MOTOR NETT. WT.		Kg.	
INSULATION CLASS			
TEMPERATURE RISE		°C	
DESIGN AMBIENT TEMPERATURE		°C	
HEATER WATTS & VOLTS		WATTS,	VOLTS

REMARKS

BROOK CROMPTON
PRELIMINARY

Large Industrial Motors
Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES

THIRD ANGLE PROJECTION

BROOK CROMPTON

Large Industrial Motors
GUISELEY, LEEDS, LS20 9NZ.

DRG. No.	M22085		
REVISION:		DATE	