



ENLARGED VIEW OF
SHAFT EXTENSION

NOTE: -
 TERMINAL BOX CAN BE TOP OR RIGHT
 HAND SIDE MOUNTED BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
HP	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT.	Kg.	
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		VOLTS

REMARKS

BROOK CROMPTON
PRELIMINARY

Large Industrial Motors
Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES

THIRD ANGLE
PROJECTION

BROOK CROMPTON

Large Industrial Motors
GUISELEY, LEEDS, LS20 9NZ.

NOTE !
 * ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
 PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
 INTENTION TO USE RIGID COUPLINGS AND DRIVEN
 MACHINES WITHOUT ENDTPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/C FACE MOUNTED INCH A. C. MOTOR
 TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.
 FITTED WITH SIDE MOUNTED TERMINAL BOX
 FRAME SIZE: - WNDF504Z.

SCALE	1:10	DATE
DRAWN	B. THOMAS	23.6.94
CHECKED	B. J. T.	23.6.94
APPROVED	I. J. W.	23.6.94

DRG. No.	M9719	
REVISION:		DATE