



ENLARGED VIEW OF  
SHAFT EXTENSION.  
(SCALE 1:3).

NOTE! TERMINAL BOX CAN BE TOP  
MOUNTED BY REFITTING FEET 90°  
IN APPROPRIATE DIRECTION.  
CABLE ENTRY CAN BE SUPPLIED IN ANY ONE  
OF FOUR POSITIONS AT 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
kW	RPM.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	DE.	NDE.
MOTOR NETT. WT. Kg.		
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS		
WATTS,		VOLTS

REMARKS  
FITTED WITH FLARED CABLE ENTRY.



ALL DIMENSIONS IN INCHES



Large Industrial Motors  
GUISELEY, LEEDS, LS20 9NZ.

NOTE 1  
2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST  
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR  
INTENTION TO USE RIGID COUPLINGS AND DRIVEN  
MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/FLANGE MOUNTED INCH A.C.  
MOTOR TO NEMA STANDARD MG1. TOTALLY ENCLOSED FAN COOLED.  
SIDE MOUNTED TERMINAL BOX.  
FRAME SIZE: W-DF444TD-E (4 POLE UP.)

SCALE	1:8	DATE
DRAWN	M.E	17.4.00
CHECKED	J.M.L	17.4.00
APPROVED	J.M.L	17.4.00

DRG. No.	M21930	
REVISION:	DATE	