



M10 EXTERNAL EARTH POSITION. (SHOWN DOTTED TO REAR OF TERMINAL BOX.)

2 LIFTING LUGS DIAGONALLY OPPOSITE.

4 HOLES  $\phi$  .8125 EQUALLY SPACED ON 20 P. C. D.

4 HOLES FOR .75 BOLTS.

NOTE! TERMINAL BOX CAN BE TOP MOUNTED BY REFITTING FEET 90° IN APPROPRIATE DIRECTION. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90° INTERVALS.

CUSTOMER			
ORDER No.			
SERIAL No.			
FRAME SIZE			
kW		RPM.	
Hz		PHASE 3	
VOLTS		POLES	
BRGS.		DE. NDE.	
MOTOR NETT. WT.		Kg.	
INSULATION CLASS			
TEMPERATURE RISE °C			
DESIGN AMBIENT TEMPERATURE °C			
HEATER WATTS & VOLTS		WATTS, VOLTS	

REMARKS

**BROOK CROMPTON**  
PRELIMINARY

Large Industrial Motors  
Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES

THIRD ANGLE PROJECTION

**BROOK CROMPTON**

Large Industrial Motors  
GUISELEY, LEEDS, LS20 9NZ.

NOTE 1  
2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/FLANGE MOUNTED INCH A. C. MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED. FITTED WITH SIDE MOUNTED TERMINAL BOX. FRAME SIZE: W-DF445TD-E (4 POLE UP.)

SCALE	1:8	DATE
DRAWN	M.E	6.7.00
CHECKED	J.M.L	6.7.00
APPROVED	J.M.L	6.7.00

DRG. No.	M22084
REVISION:	DATE